

## Application :

- For vertical installation of steel, copper and PVC pipes nail hanger can be used.
- Suitable for installation without vibration control requirements.

## Technical Specification :

- Suitable upto 343°C (650° F) .
- Hot dip Galvanised. As per ASTM A153 standard.
- Electro Galvanised. As per ASTM B 663 standard.

## Construction Feature :

- Made with steel.
- SS - 304/316 can be manufactured on request.
- Hot dip Galvanised. 30 to 120 micron
- Finished with zinc plating Electrogalvanized.



Product Code	Size (Inch)	Diameter (mm)	Screw Size
SENLH 01	½"	22	M6 x M20
SENLH 02	¾"	28	M6 x M20
SENLH 03	1"	35	M6 x M20
SENLH 04	1.25"	42	M6 x M20
SENLH 05	1½"	48	M6 x M20
SENLH 06	54 mm	54	M6 x M20
SENLH 07	2"	60	M6 x M20
SENLH 08	67mm	67	M6 x M20
SENLH 09	2 ½"	75	M6 x M20
SENLH 10	82mm	82	M6 x M20
SENLH 11	3"	90	M6 x M20
SENLH 12	3 ½"	101	M6 x M20
SENLH 13	108mm	108	M6 x M20
SENLH 14	4"	114	M6 x M20
SENLH 15	126mm	126	M6 x M20
SENLH 16	5"	141	M6 x M20
SENLH 17	6"	168	M6 x M20
SENLH 18	190mm	190	M6 x M20
SENLH 19	8"	219	M6 x M20