

# U BOLT

## Application :

U-Bolts are used to secure piping to structural members. When the piping system is above the structural member, the U-Bolt restricts lateral movement and upward movement while allowing axial movement of the piping.

## Construction:

U-Bolt is provided with four standard hex nuts and has a longer straight threaded length.

## Material:

Steel. Also other materials can also be provided on request

## Maximum Temperature:

400°C (752° F)

## Finish Available:

Plain, Hot Dip Galvanized, Electro-Galvanized.



Product Code	Pipe Size (Inch)	Diameter (mm)	Material Dimension (mm)			Bolt Size (mm)	Max Load (kg)
			Rod Dia. W	Height L	Thread Length T		
SEUB 01	½"	21.5	21	65	50	M10	550
SEUB 02	¾"	26.8	27	77	50	M10	550
SEUB 03	1"	33.2	34	85	50	M10	550
SEUB 04	1 ¼"	42.3	43	93	50	M10	550
SEUB 05	1 ½"	48.3	48	100	50	M10	550
SEUB 06	2"	60.2	60	110	50	M10	550
SEUB 07	2 ½"	73.0	76	127	50	M12	900
SEUB 08	3"	88.8	89	140	50	M12	900
SEUB 09	4"	114.1	115	165	50	M12	900
SEUB 10	5"	141.3	140	190	50	M12	900
SEUB 11	6"	168.3	168	220	50	M12	900
SEUB 12	8"	219.2	219	295	75	M16	1900
SEUB 13	10"	273.1	273	370	100	M20	3200