

U BOLT WITH LINING

Application :

U-Bolts are used to secure piping to structural members. U-Bolt provides vertical support and restricts lateral movement, the U-Bolt restricts lateral movement and upward movement while allowing axial movement of the piping.

Construction:

U-Bolt is provided with four standard hex nuts and has a longer straight threaded length. Reduces noise upto 18dB.

Material:

Steel. Also other materials can also be provided on request

Maximum Temperature: 140°C

Minimum Temperature: -40°C

Finish Available:

Plain, Hot Dip Galvanized, Electro-Galvanized.



Product Code	Pipe Size (Inch)	Diameter (mm)	Material Dimension (mm)			Bolt Size (mm)	Max Load (kg)
			Rod Dia. W	Height L	Thread Length T		
SEUBL 01	½"	21.5	21	65	50	M10	580
SEUBL 02	¾"	26.8	27	77	50	M10	580
SEUBL 03	1"	33.2	34	85	50	M10	580
SEUBL 04	1 ¼"	42.3	43	93	50	M10	580
SEUBL 05	1 ½"	48.3	48	100	50	M10	580
SEUBL 06	2"	60.2	60	110	50	M10	580
SEUBL 07	2 ½"	73.0	76	127	50	M12	950
SEUBL 08	3"	88.8	89	140	50	M12	950
SEUBL 09	4"	114.1	115	165	50	M12	950
SEUBL 10	5"	141.3	140	190	50	M12	950
SEUBL 11	6"	168.3	168	220	50	M12	950
SEUBL 12	8"	219.2	219	295	75	M16	1930
SEUBL 13	10"	273.1	273	370	100	M20	3280