

U STRAP HANGER WITH LINING

Application :

A Standard Pipe Strap is recommended for supporting a piping system with fittings vertically or horizontally to walls or ceilings. It can be used as a restrainer when installed on top of structural wood beams for beam, for limiting pipe movements due to thrust loads during sprinkler system start-up.

Construction:

A Standard Pipe Strap consists of a piece of carbon steel shaped to hold the pipe down to walls or ceilings. Reduce noise upto 18 dB

Material:

Steel. Also other materials can also be provided on request

Maximum Temperature: 120° C

Minumum Temperature : -40° C

Finish Available:

Plain, Hot Dip Galvanized, Electro-Galvanized.



Product Code	Pipe Size (Inch)	Diameter (mm)	Screw Size	Max Load (kg)
SEUSHWL 01	½"	21.5	M8	560
SEUSHWL 02	¾"	26.5	M8	560
SEUSHWL 03	1"	33.2	M8	560
SEUSHWL 04	1 ¼"	42.3	M8	506
SEUSHWL 05	1 ½"	48.3	M8	560
SEUSHWL 06	54mm	54	M8	560
SEUSHWL 07	2"	60.2	M8	560
SEUSHWL 08	2 ½"	73.0	M8	650
SEUSHWL 09	82mm	82	M8	650
SEUSHWL 10	3"	89.0	M8	650
SEUSHWL 11	3 ½"	101.8	M8	650
SEUSHWL 12	108mm	108	M8	650
SEUSHWL 13	4"	114.6	M8	650
SEUSHWL 14	126mm	126	M8	650
SEUSHWL 15	5"	141.5	M10	650
SEUSHWL 16	148mm	148	M10	650
SEUSHWL 17	155mm	155	M10	650
SEUSHWL 18	6"	168.9	M10	650
SEUSHWL 19	179mm	179	M10	650
SEUSHWL 20	190mm	190	M10	830
SEUSHWL 21	205mm	205	M10	830
SEUSHWL 22	8"	219.5	M10	830
SEUSHWL 23	230mm	230	M10	830
SEUSHWL 24	241mm	241	M12	1330
SEUSHWL 25	263mm	263	M12	1330
SEUSHWL 26	10"	273	M18	1330